



SUZUKI GSXR1000 `05-`06
ID: 20051012/20051017

Installing:

Left side:

Right side:
























1. Contact a specialized service, do not install the cage yourself!
2. For installing cage is necessary to cut holes in fairing in points №3 and №4
3. Remove original bolt in point №1
4. Remove original bolt in point №5
5. Attach left side of cage to points №1 and №5.
6. Screw lightly left side of cage with bolt M10x1,25x100 in point №1
7. Insert through ear of cage rod M10x330 in point №5
8. Remove original bolt in point №2
9. Attach right side of cage in point №2 and rod in point №6.
10. Screw lightly right side of cage with bolt M10x1,25x70 in point №2
11. Install brace 180mm between points №3 and №4 and fix with bolts M10x1,25x30
12. Tighten the nut in point №6
13. Tighten the fasteners according to the table.

Install Sliders in points №1 and №2 and fix them with screws (In case 20051017 use Damper sliders)

Tightening torques Nm		
Thread	Connection type	
	Steel	Aluminum
M6	10	6
M8	24	20
M10	48	35
M12	56	45

Component table with according numbers in the photo:

№	Item				
1	Bolt M10x1,25x100	Spring washer	Washer	Slider	
					
2	Bolt M10x1,25x70	Spring washer	Washer	Slider	
					
3	Bolt M10x1,25x30	Spring washer	Washer	Rod L=180 mm	
					
4	Bolt M10x1,25x30	Spring washer	Washer		
					
5	Brace M10x330	Nut	Washer		
					
6		Nut	Washer		
		